



Product Portfolio



Application	Article	Coating	Weight	Tensile strength	Tear resistance DIN EN 17679	Adhesion	Other attributes
Tarpaulins for truck & trailers	vectaplan 8/8 FR H5671	PVC	650 g/m ² 19 oz/yd ²	≥ 2500/2500 N/5 cm ≥ 286/286 lbf/inch	≥ 250/250 N ≥ 56/56 lbf	≥ 100 N/5 cm ≥ 11 lbf/inch	FR acc. to DIN 4102-1 B1
	vectaplan 8/8 H5518	PVC	650 g/m ² 19 oz/yd ²	≥ 2500/2500 N/5 cm ≥ 286/286 lbf/inch	≥ 250/250 N ≥ 56/56 lbf	≥ 100 N/5 cm ≥ 11 lbf/inch	
	 vivatex® vectaplan 8/8 H7718	PVC	650 g/m ² 19 oz/yd ²	≥ 2500/2500 N/5 cm ≥ 286/286 lbf/inch	≥ 250/250 N ≥ 56/56 lbf	≥ 100 N/5 cm ≥ 11 lbf/inch	recycled yarns; CO ₂ compensated
	vectaplan 9/9 H5560	PVC	680 g/m ² 20 oz/yd ²	≥ 3000/3000 N/5 cm ≥ 343/343 lbf/inch	≥ 300/300 N ≥ 67/67 lbf	≥ 100 N/5 cm ≥ 11 lbf/inch	
Side curtain	vectaplan panama* H5551	PVC	900 g/m ² 27 oz/yd ²	≥ 4000/4000 N/5 cm ≥ 457/457 lbf/inch	≥ 300/300 N** ≥ 67/67 lbf	≥ 100 N/5 cm ≥ 11 lbf/inch	
	 vivatex® vectaplan panama H7751	PVC	900 g/m ² 27 oz/yd ²	≥ 4000/4000 N/5 cm ≥ 457/457 lbf/inch	≥ 300/300 N** ≥ 67/67 lbf	≥ 100 N/5 cm ≥ 11 lbf/inch	recycled yarns; CO ₂ compensated
Roof tarpaulin	tectaplan 695 hp H6581	PVC	695 g/m ² 20 oz/yd ²	≥ 3000/3000 N/5 cm ≥ 343/343 lbf/inch	≥ 300/300 N ≥ 67/67 lbf	≥ 100 N/5 cm ≥ 11 lbf/inch	
	traintarp 750 FR H5768	PVC	750 g/m ² 22 oz/yd ²	≥ 3000/3000 N/5 cm ≥ 343/343 lbf/inch	≥ 300/300 N ≥ 67/67 lbf	≥ 100 N/5 cm ≥ 11 lbf/inch	FR acc. to DIN 4102-1 B1
	traintarp 900 FR H5673	PVC	900 g/m ² 27 oz/yd ²	≥ 4000/4000 N/5 cm ≥ 457/457 lbf/inch	≥ 550/500 N ≥ 124/112 lbf	≥ 100 N/5 cm ≥ 11 lbf/inch	FR acc. to DIN 4102-1 B1
Heat resistant trailer covers	vectaplan heat cover H8516	PU	465 g/m ² 14 oz/yd ²	≥ 5000/4500 N/5 cm ≥ 571/514 lbf/inch	≥ 850/800 N ≥ 191/180 lbf	–	bending stiffness, abrasion and heat resistance (up to 180°C)

Light fastness: 7-8 | temperature resistance: -30°C up to +70°C (-22°F up to 158°F) | Flame retardancy ≤ 100 mm/min | *complies with DIN 12641-2 | ** DIN EN 1875-3

Further items, colors and specifications on request. Product information without legal binding. Subject to alterations without prior notice; errors including printer's errors. The product is subject to fluctuations. Certain data are rounded up to the nearest full value. FR certificates may not apply to all colors.



ClimatePartner
certified product
climate-id.com/E6CMHZ



DURABLE & BRILLIANT SOLUTIONS ON WHEELS.

HEYcargo® materials are used as extremely durable and colourfast truck and trailer tarpaulins and convince by their particularly smooth glossy surface and excellent suitability for printing and pasting.

Easy to secure, glossy surface and excellent soiling behaviour available up to 320 cm width, Heytex truck tarps ensure safe transport in all conditions, offering reliable, cost-effective coverage on every journey

Another highlight of the HEYcargo® collection: All tarpaulins are manufactured in accordance with RAL standards – almost any color is possible. Unattractive colour variations between vehicle and tarpaulin are things of the past.



- very good flatness
- easy weldability (high-frequency, hot air, wedge)
- low smoke and odour development during processing
- easy-to-clean high gloss coating
- wide RAL range available ex stock at short notice
- very good printability
- brilliant, kink resistant “Silver”; best silver on the market

Additionally to the standard range, we also offer more sustainable materials under the „vivatex®“ label. vivatex® is subject to continuous expansion and development and even now consist of at least 20% recycled or renewable raw materials, which sustainably reduces the CO₂ footprint.



Application example: shutterstock



MADE IN
GERMANY



HEYTEX.COM